

EL FABRICANTE:

S.A.C.I.D.

Raval dels Torrents, Par. 4 DC-163
08297 CASTELLGALÍ
BARCELONA (ESPAÑA)



INFORMA QUE EL EPI DESCRITO A CONTINUACIÓN:

KORDA'S ANNA 10,5mm

NORMA QUE CUMPLE: DINAMICA SIMPLE

EN892:2012+A12016

Nº CERTIFICADO: 0082/483/136/09/19/0982

**ÉS CONFORME A LAS DISPOSICIONES DEL REGLAMENTO UE2016-425,
CON LOS SIGUIENTES DATOS TÉCNICOS DE HOMOLOGACIÓN :**

DATO	VALOR
Diámetro	10,5 mm
Peso por metro	73 g/m
Porcentaje Alma	0,71
Deslizamiento funda	0 mm
Alargamiento	0,04
Fuerza de choque (F2)	950 daN
Nº choques (F2)	>5 (=10)
Elasticidad dinámica	30%

REALIZADO EN: CASTELLGALÍ

CON FECHA: 29/06/2020

FIRMA:

Jose Joaquín Castaño Lacruz
Responsable Técnico



TECHNICAL DATA REPORT

THE MANUFACTURER:

S.A.C.I.D.

Raval dels Torrents, Par. 4 DC-163
08297 CASTELLGALÍ
BARCELONA (SPAIN)



INFORMS THAT THE FOLLOWING PPE :

KORDA'S - ANNA 10,5

NORM WHICH MEETS: **SIMPLE DYNAMIC**
EN892:2012+A12016

N. CERTIFICATION: **0082/483/136/09/19/0982**

**SATISFIES THE DISPOSITIONS OF THE REGULATION UE2016-425,
WITH THE FOLLOWING TECHNICAL DATA OF CERTIFICATION:**

Diametre	10,5 mm
Weight per metre	73 g/m
Core Percentage	0,71
Sheath Slippage	0 mm
Elongation	0,04
Impact Force (F2)	950 daN
Number of Falls (F2)	>5 (=10)
Dynamic elongation	0,296

ISSUED IN: CASTELLGALÍ

DATE: 29/06/2020

SIGNATURE:

Jose Joaquín Castaño Lacruz
Technical Director