



INFORME DATOS TÉCNICOS

EL FABRICANTE:

S.A.C.I.D.

Raval dels Torrents, Par. 4 DC-163

08297 CASTELLGALÍ

BARCELONA (ESPAÑA)



INFORMA QUE EL EPI DESCRITO A CONTINUACIÓN:

KORDA'S KRIS 10,1 mm

NORMA QUE CUMPLE: **DINAMICA SIMPLE**

EN892:2012+A12016

Nº CERTIFICADO: **0082/483/136/09/19/0983**

**ÉS CONFORME A LAS DISPOSICIONES DEL REGLAMENTO UE2016-425,
CON LOS SIGUIENTES DATOS TÉCNICOS DE HOMOLOGACIÓN :**

DATO	VALOR
Diámetro	10,2 mm
Peso por metro	66,0 g/m
Peso alma	44,0 g/m
Porcentaje alma	67,0%
Deslizamiento funda	0 mm
Alargamiento	8,0%
Fuerza de choque (F2)	830 daN
Nº caídas (F2)	800%
Elasticidad dinámica	32,50%

REALIZADO EN: CASTELLGALÍ

CON FECHA: 29/06/2020

FIRMA:

Jose Joaquín Castaño Lacruz
Responsable Técnico



TECHNICAL DATA REPORT

THE MANUFACTURER:

S.A.C.I.D.
Raval dels Torrents, Par. 4 DC-163
08297 CASTELLGALÍ
BARCELONA (SPAIN)



INFORMS THAT THE FOLLOWING PPE :

KORDA'S - KRIS 10,1

NORM WHICH MEETS: **DYNAMIC SINGLE ROPE**
EN892:2012+A12016

N. CERTIFICATION: **0082/483/136/09/19/0983**

**SATISFIES THE DISPOSITIONS OF THE REGULATION UE2016-425,
WITH THE FOLLOWING TECHNICAL DATA OF CERTIFICATION:**

Diametre	10,2 mm
Weight per metre	66,0 g/m
Core Weight	44,0 g/m
Core Percentage	67%
Sheath Slippage	0 mm
Elongation	8%
Impact Force (F2)	830 daN
Number of Falls (F2)	8
Dynamic elongation	33%

ISSUED IN: CASTELLGALÍ

DATE: 29/06/2020

SIGNATURE:

Jose Joaquín Castaño Lacruz
Technical Director